



CONSISTOMETER

General Information

The Consistometer is a low cost, durable, instrument for accurately checking laboratory or production samples against consistency, viscosity or flow rate standards.

It uses little bench space and is yet probably the simplest, most accurate method of conducting a variety of flow associated tests. It is already widely used in the chemical, paint, cosmetic and food processing industries.

The consistometer provides a single parameter for a variety of flow tests which can be carried out over any period under as near identical conditions as possible.

The Consistometer or Bostwick Consistometer is manufactured from stainless steel engraved with a series of precise graduations at 0.5 cm intervals.

To ensure accurate reproducibility, the instrument is levelled using the adjustment screws and spirit level.



Advantages

- Low cost
- Ease of use
- Suitable for a variety of tests
- Provides a consistent platform for test
- Requires only 75 ml of sample
- Stainless steel construction
- Engraved graduations for accurate results
- Leveling screws and spirit level enable accurate set up
- Available as standard or extended version

Specifications

Application	checking laboratory or production samples against consistency, viscosity or flow rate standards
Length	standard version: 355 mm extended version: 414 mm
Trough length	standard version: 240 mm extended version: 300 mm
Width	standard version: 84 mm extended version: 84 mm
Height	standard version: 110 - 139 mm extended version: 110 - 139 mm

Function

A measured sample, usually 75 ml, is placed in the reservoir behind the gate of the consistometer.



Product Information



CONSISTOMETER

The gate is released, by pressing the lock release lever - the spring action ensures it opens instantaneously.

As the fluid flows down the instrument its progress can be accurately measured using the graduated scale. By comparing the flow rate to specified time periods the physical properties of the sample can be calculated.