



**Enables remote sound level readings**

Coiled probe extends to 9'. Features both RS232 computer interface and AC output. Also has A and C decibel frequency weighting scales, fast or slow time weighting, hold, peak hold, and min/max functions. Meets IEC 61672 class 2 and ANSI S1.4 type 2 frequency and time weighting specifications. Covers 30 ~ 130 dB in both manual and auto-ranging scales with 0.1 dB resolution and an accuracy of ±1.5 dB. Calibrate in compliance with OSHA using Acoustical Calibrator 850016. Has a fold-out easel back and tripod screw. Comes ready to use with a windscreen, calibration tool, instructions and 9V battery in a hard-shell, foam-lined carrying case.

DIM: 8" × 2½" × 1" (50 × 68 × 30 mm). WEIGHT: 8 oz (225 g) with battery.



No.	Description
<b>840012</b>	<b>Detachable Probe Sound Meter</b>
<b>840012C</b>	<b>Detachable Probe Sound Meter Certified</b>
840057	RS232 Computer Cable
840090	Water Resistant Instrument Pouch
840091	Windscreen Replacement
840092	Benchtop Tripod
840093	Field Tripod
840094	RS232 to USB Adaptor Cable
850016	2-Pt. Acoustical Calibrator
850080	Software